

SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

Product ID: MISCO SLIK HEAT STABLE SILICONE
Product Name: MISCO SLIK HEAT STABLE SILICONE
Revision Date: Oct 12, 2018
Version: 2.0
Distributor's Name: MISCO INDUSTRIAL, LLC
Address: 109 Space Park N, Goodlettsville, TN 37072
Emergency Phone: 1-800-535-5053
Information Phone Number: (615) 334-1861
Fax:
Product/Recommended Uses: Silicone lubricant

Date Printed: 8/20/19
Supersedes Date: May 03, 2018

SECTION 2) HAZARDS IDENTIFICATION**Classification**

Aerosols Category 1
Aspiration Hazard - Category 1
Eye Irritation - Category 2A
Gases Under Pressure Compressed Gas
Reproductive Toxicity (Fertility) - Category 2
Skin Irritation - Category 2
Specific Target Organ Toxicity - Repeated Exposure - Category 2
Specific Target Organ Toxicity -Single Exposure (Narcotic Effects) - Category 3
Specific Target Organ Toxicity -Single Exposure (Respiratory Tract Irritation) - Category 3
Percentage of the mixture consisting of ingredient(s) of unknown oral toxicity: 34.6%
Percentage of the mixture consisting of ingredient(s) of unknown dermal toxicity: 94.6%
Percentage of the mixture consisting of ingredient(s) of unknown inhalation toxicity: 71%

Pictograms**Signal Word**

Danger

Hazardous Statements - Physical

H222 - Extremely flammable aerosol
H280 - Contains gas under pressure; may explode if heated

Hazardous Statements - Health

H319 - Causes serious eye irritation

H315 - Causes skin irritation

H361 - Suspected of damaging fertility.

H304 - May be fatal if swallowed and enters airways

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements - General

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P103 - Read label before use.

Precautionary Statements - Prevention

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P280 - Wear protective gloves, protective clothing, eye protection and face protection.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P271 - Use only outdoors or in a well-ventilated area.

P260 - Do not breathe mist, vapors or spray.

P264 - Wash hands thoroughly after handling.

Precautionary Statements - Response

P314 - Get medical attention if you feel unwell.

P308 + P313 - IF exposed or concerned: Get medical attention.

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 - Call a POISON CENTER or doctor if you feel unwell.

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P331 - Do NOT induce vomiting.

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.

P362 + P364 - Take off contaminated clothing and wash it before reuse.

P332 + P313 - If skin irritation occurs: Get medical attention.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical attention.

Precautionary Statements - Storage

P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P403 + P405 - Store in a well-ventilated place. Store locked up.

Precautionary Statements - Disposal

P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplementary Information

DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE: Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Please refer to the SDS for additional information. Keep out of reach of children. Keep upright in a cool, dry place. Do not discard empty can in trash compactor.

SECTION 3) COMPOSITION, INFORMATION ON INGREDIENTS

CAS	Chemical Name	% By Weight
0000067-64-1	ACETONE	25% - 50%
0000110-54-3	HEXANE	10% - 25%
0000074-98-6	PROPANE	10% - 25%
0000107-83-5	2-METHYL PENTANE	10% - 25%
0000096-14-0	3-METHYL PENTANE	1.0% - 5%
0000079-29-8	2,3-DIMETHYL BUTANE	1.0% - 5%
0000110-82-7	CYCLOHEXANE	1.0% - 3%
0000075-83-2	2,2-DIMETHYL BUTANE	1.0% - 3%
0000287-92-3	CYCLOPENTANE	0.1% - 1.0%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

SECTION 4) FIRST-AID MEASURES

Inhalation

If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.

Eye Contact

Wash immediately with large volumes of fresh water for at least 15 minutes. Get medical attention.

Skin Contact

Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse.

Ingestion

Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing media suitable for surrounding fire.

Unsuitable Extinguishing Media

None known.

Specific Hazards in Case of Fire

Closed containers may explode from internal pressure build-up when exposed to extreme heat and discharge contents. Liquid content of container will support combustion. Overexposure to decomposition products may cause a health hazard. Symptoms may not be readily apparent. Obtain medical attention. Hazardous decomposition products include carbon dioxide, carbon monoxide, and other toxic fumes.

Fire-Fighting Procedures

Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.

Special Protective Actions

Wear goggles and use a self-contained breathing apparatus. If water is used, fog nozzles are preferred.

SECTION 6) ACCIDENTAL RELEASE MEASURES

Emergency Procedure

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

Small spill: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Recommended Equipment

Clean up with an absorbent material and place in closed containers for disposal.

Personal Precautions

Wear appropriate protective equipment (see Section 8).

Environmental Precautions

Stop spill/release if it can be done safely.

SECTION 7) HANDLING AND STORAGE

General

Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor, mist or spray. Do not swallow. Avoid breathing gas. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.

Ventilation Requirements

Use in a well-ventilated place.

Storage Room Requirements

Store and use in a cool, dry, well-ventilated area. Do not store above 120°F. See product label for additional information.

SECTION 8) EXPOSURE CONTROLS, PERSONAL PROTECTION

Eye Protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, vapors or spray. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin Protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products

if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Respiratory Protection

Avoid breathing vapors. In restricted areas, use approved chemical/mechanical filters designed to remove a combination of particles and vapor. In confined areas, use an approved air line respirator or hood. A self-contained breathing apparatus is required for vapor concentrations above PEL/TLV limits.

Appropriate Engineering Controls

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Chemical Name	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)	OSHA Tables (Z1, Z2, Z3)	OSHA Carcinogen	OSHA Skin designation	NIOSH TWA (ppm)	NIOSH TWA (mg/m3)	NIOSH STEL (ppm)	NIOSH STEL (mg/m3)	NIOSH Carcinogen
2,2-DIMETHYL BUTANE												
2,3-DIMETHYL BUTANE												
2-METHYL PENTANE												
3-METHYL PENTANE												
ACETONE	1000	2400			1			250	590			
CYCLOHEXANE	300	1050			1			300	1050			
CYCLOPENTANE								600	1720			
HEXANE	500	1800			1			50	180			
PROPANE	1000	1800			1			1000	1800			

Chemical Name	ACGIH TWA (ppm)	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)
2,2-DIMETHYL BUTANE	500		1000	
2,3-DIMETHYL BUTANE	500		1000	
2-METHYL PENTANE	500		1000	
3-METHYL PENTANE	500		1000	
ACETONE	250		500	
CYCLOHEXANE	100			
CYCLOPENTANE	600	1720		
HEXANE	50	176		
PROPANE	See Appendix F: Minimal Oxygen Content			

(C) - Ceiling limit

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Density	5.675 lb/gal
Density VOC	3.405 lb/gal
% VOC	60.00%
<hr/>	
Appearance	Liquid
Odor Threshold Odor	N.A.
Description	N.A.
pH	7
Water Solubility	N.A.
Flammability	Flash point below 73°F/23°C
Flash Point Viscosity,	-23 °C
Kinematic Lower	<20.5 cSt (40°C)
Explosion Level Upper	1%
Explosion Level Vapor	12.8%
Density	1.55 [Air = 1]
Melting Point	N.A.
Freezing Point	N.A.
Low Boiling Point	N.A.
High Boiling Point	N.A.
Decomposition Pt	N.A.
Auto Ignition Temp	N.A.
Evaporation Rate	9.1 (butyl acetate = 1)
Vapor Pressure	101.3 kPa (20°C)

SECTION 10) STABILITY AND REACTIVITY

Stability

The product is stable under normal storage conditions.

Conditions to Avoid

Keep away from heat, sparks, extreme temperature, flame, other sources of ignition and incompatible materials.

Incompatible Materials

Strong oxidizers.

Hazardous Reactions/Polymerization

None known.

Hazardous Decomposition Products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11) TOXICOLOGICAL INFORMATION

Skin Corrosion/Irritation

Causes skin irritation

Serious Eye Damage/Irritation

Causes serious eye irritation

Carcinogenicity

No data available

Germ Cell Mutagenicity

No data available

Reproductive Toxicity

Suspected of damaging fertility.

Respiratory/Skin Sensitization

No data available

Specific Target Organ Toxicity - Single Exposure

May cause drowsiness or dizziness

May cause respiratory irritation

Specific Target Organ Toxicity - Repeated Exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard

May be fatal if swallowed and enters airways

Acute Toxicity

No data available

Potential Health Effects - Miscellaneous

0000067-64-1 ACETONE

The following medical conditions may be aggravated by exposure: lung disease, eye disorders, skin disorders. Overexposure may cause damage to any of the following organs/systems: blood, central nervous system, eyes, kidneys, liver, respiratory system, skin.

0000110-82-7 CYCLOHEXANE

LD50 (oral, rat): 8-39 mL/kg (6200 to 30400 mg/kg) (3)

LD50 (oral, mouse): 1300 mg/kg (3)

LD50 (dermal, rabbit): Greater than 18000 mg/kg (4)

0000067-64-1 ACETONE

LC50 (male rat): 30000 ppm (4-hour exposure); cited as 71000 mg/m³ (4-hour exposure) (29)

LC50 (male mouse): 18600 ppm (4-hour exposure); cited as 44000 mg/m³ (4-hour exposure) (29)

LD50 (oral, female rat): 5800 mg/kg (24)

LD50 (oral, mature rat): 6700 mg/kg (cited as 8.5 mL/kg) (31)

LD50 (oral, newborn rat): 1750 mg/kg (cited as 2.2 mL/kg) (31)

LD50 (oral, mouse): 3000 mg/kg (32, unconfirmed)

LD50 (dermal, rabbit): Greater than 16000 mg/kg cited as 20 mL/kg (30)

0000110-54-3 HEXANE

LC50 (male rat): 38500 ppm (4-hour exposure); cited as 77000 ppm (271040 mg/m³) (1-hour exposure) (15)

LC50 (rat): 48000 ppm (4-hour exposure) (16)

LC50 (rat): 73680 ppm (260480 mg/m³) (4-hour exposure) (n-hexane and isomers) (1,3)

LD50 (oral, 14-day old rat): 15840 mg/kg (3)

LD50 (oral, young rat): 32340 mg/kg (3)

LD50 (oral, adult rat): 28700 mg/kg (3,16)

SECTION 12) ECOLOGICAL INFORMATION

Toxicity

No data available

Persistence and Degradability

0000067-64-1 ACETONE

91% readily biodegradable, Method: OECD Test Guideline 301B

Bio-Accumulative Potential

000067-64-1 ACETONE

Does not bioaccumulate

Mobility in Soil

No data available.

Other Adverse Effects

No data available.

SECTION 13) DISPOSAL CONSIDERATIONS

Waste Disposal

Under RCRA, it is the responsibility of the user of the product, to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state, and local laws.

Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

SECTION 14) TRANSPORT INFORMATION

U.S. DOT Information

UN number: UN1950

Proper shipping name: Aerosols, flammable, (each not exceeding 1 L capacity) (LTD QTY)

Hazard class: 2.1

Packaging group: N.A.

Hazardous substance (RQ): No Data Available

Toxic-Inhalation Hazard: No Data Available

Marine Pollutant: No Data Available

Note / Special Provision: No Data Available

IMDG Information

UN number: UN1950

Proper shipping name: Aerosols, flammable, (each not exceeding 1 L capacity) (LTD QTY)

Hazard class: 2.1

Packaging group: N.A.

Marine Pollutant: No Data Available

Note / Special Provision: No Data Available

IATA Information

UN number: UN1950

Hazard class: 2.1

Packaging group: N.A.

Proper shipping name: Aerosols, flammable, (each not exceeding 1 L capacity)

Note / Special Provision: No Data Available

SECTION 15) REGULATORY INFORMATION

CAS	Chemical Name	% By Weight	Regulation List
0000067-64-1	ACETONE	25% - 50%	CERCLA,SARA312,TSCA,RCRA,ACGIH,OSHA
0000110-54-3	HEXANE	10% - 25%	CERCLA,HAPS,SARA312,VOC,TSCA,ACGIH,CA_Prop65 - California Proposition 65,OSHA
0000074-98-6	PROPANE	10% - 25%	SARA312,VOC,TSCA,ACGIH,OSHA
0000107-83-5	2-METHYL PENTANE	10% - 25%	SARA312,VOC,TSCA,ACGIH
0000096-14-0	3-METHYL PENTANE	1.0% - 5%	SARA312,VOC,TSCA,ACGIH
0000079-29-8	2,3-DIMETHYL BUTANE	1.0% - 5%	SARA312,VOC,TSCA,ACGIH
0000110-82-7	CYCLOHEXANE	1.0% - 3%	CERCLA,SARA312,VOC,TSCA,RCRA,ACGIH,OSHA
0000075-83-2	2,2-DIMETHYL BUTANE	1.0% - 3%	SARA312,VOC,TSCA,ACGIH
0000287-92-3	CYCLOPENTANE	0.1% - 1.0%	SARA312,VOC,TSCA,ACGIH

SECTION 16) OTHER INFORMATION

Glossary


* There are points of differences between OSHA GHS and UN GHS. In 90% of the categories, they can be used interchangeably, but for the Skin Corrosion/Irritant Category and the Specific Target Organ Toxicity (Single and Repeated Exposure) Categories. In these cases, our system will say UN GHS.

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG- Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

HMIS

Health	* 2
FLAMMABILITY	4
Physical Hazard	0
Personal Protection	B

NFPA



(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks

Version 2.0:

Revision Date: Oct 12, 2018

DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.